



TEX HEAVY DUTY DIESEL ENGINE OIL

DESCRIPTION AND APPLICATIONS

TEX Heavy Duty Diesel Engine Oil specifically formulated to exceed the lubrication requirements of the modern diesel engines and 4-cycle gasoline engines (excluding aircraft). It contains selected base stocks and high performance modern additives to provide an outstanding engine performance. This product is recommended for engines operating under extended oil drain programs.

TEX Heavy Duty Diesel Engine Oil meets or exceeds:

API CI-4,CH-4, CG-4, CF-4, CF / SJ (SAE 15W40)

API CF-2, CF / SJ (SAE 30, 40, 50)

Product Specifications:

Test	Typical Results			
	15w-40	30	40	50
Specific Gravity (60°F)	0.880	0.882	0.887	0.888
Viscosity, @40°C, cSt	119.2	77.6	136.7	170.9
Viscosity, @ 100°C, cSt	15.1	10.3	14.6	16.9
Viscosity Index	131	116	106	105
Flash Point, °C (°F)	221 (430)	-	-	-
Pour Point, °C (°F)	-25(-13)	-18 (0)	-18 (0)	-18 (0)
CCS Viscosity @ -15°C, cP, Max.	3,500	-	-	-
Zn, ppm	1,310	1,298	1,298	1,298
TBN, min.	12.0	9.3	9.2	9.3
Color	4.5	5.5	5.5	5.5

Packaging Specifications:

Bottle	N/A
Cases/Pallet	N/A
Units/Case	N/A

Product Claims:

TEX Heavy Duty Diesel Engine Oil improves engine wear protection, lessens oil consumption, provides excellent oxidation stability and improved soot dispersancy.

Hazards:

“Empty” containers retain residue (liquid and/or vapor) and can be dangerous. Do not pressure, cut weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, or other sources of ignition. “Empty” drums should be completely drained, properly bunged, and promptly returned to a drum reconditioner.

Avoid prolonged contact with skin and frequently change soiled clothing. In case of contact, wash thoroughly with soap and water for 15 minutes or until the irritation subsides. The formation of mists should be avoided.

CAUTION: Continuous contact with used motor oil has caused skin cancer in laboratory animals. Keep out of reach of children.